



PRECISION LATHE

SSM-1340BV

Accessories & Features

Specifications

Standard Accessories

- 1. 7" 3-Jaw Chuck (177mm)
- 2. 8" 4-Jaw Chuck (203mm)
- 3. Steady Rest & Follow Rest
- 4. 4-Position Tool Post
- 5. Coolant System
- 6. Full-Length Splash Guard
- 7. Worklight
- 8. Chuck Cover
- 9. Thread Chasing Dial

Optional Accessories

- Acu-Rite 200S DRO
 (2-axis, x=0.0001" (0.00254mm) / z=0.0002" (0.00508 mm) res)*
- 2. Royal Spindle Type Live Center
- 3. BTC 3-Jaw Chuck with back plate
- 4. Taper Turning Attachment
- 5. Aloris CXA #3-BS (tool post plus 4 holders)
- 6. 5C Lever Style Collet Closer
- 7. 5C Front Mount Hand Wheel Style Collet Closer

Machine Features


- 3 hp Main Spindle Motor (2.23kw)
- Digital RPM Display for Hi/Low Gear Speed Ranges
- Capable of being run on Single Phase or 3 Phase power
- Hardened & Ground Gears and Bedways
- Jog Button

- Cast Iron Machine Bedways
- Removable Chip Pan
- Foot brake and T-Slot compound
- Inch/Metric Ruler on Tailstock
 Quill



ing Over Bed ing Over Cross Slide ing Over Gap dth of Bed tance Between Centers	SSM-1340BV 13" (330mm) 8-1/4" (210mm) 18-1/2" (470mm) 7-1/2" (190mm) 40" (1016mm)
ing Over Cross Slide ing Over Gap dth of Bed	8-1/4" (210mm) 18-1/2" (470mm) 7-1/2" (190mm)
ing Over Gap	18-1/2" (470mm) 7-1/2" (190mm)
dth of Bed	7-1/2" (190mm)
_	· ·
tance Between Centers	40" (1016mm)
	10 (101011111)
ss Slide Travel	6-3/4" (172mm)
Slide Travel	3-1/2" (90mm)
ndle Bore	1.5" (38mm)
ndle Speeds	2
ndle Speed Range	40-365 & 218-2000 rpm
ough Hole Diameter	1-9/16" (40mm)
ndle Nose	ASA D1-4 Camlock
ndle Bore Taper	MT#5
ead – Standard (Whit-worth)	34 (2-56) TPI
ead – Metric Pitch	33 (0.5-12) mm
ngitudinal Feed	0.0016"-0.046" (0.04064-0.11684 mm)
ss Feed	0.0005"-0.015" (0.0127-0.381 mm)
d Screw Diameter	7/8" (22mm)
ead Pitch	8 tpi (203 mm)
ill Travel	4" (101mm)
ill Diameter	1-9/16" (40mm)
ill Bore Taper	MT#3
in Motor	3 hp (2.23kw)
plant Pump Motor	1/8 hp (.125 kw)
chine Dimension	74" x 28" x 54" (1879 x 711 x 1371 mm)
king Dimension	77" x 30" x 60" (1955 x 762 x 1524 mm)
chine Weight	1320 lbs (598kg)
king Weight	1584 lbs (718kg)

The above specifications are for reference only, we reverse the right to alter them without further notice.





Kent Industrial USA, INC 1231 Edinger Avenue Tustin, CA 92780 USA Phone: +1.714.258.8526 E-mail: info@kentusa.com www.kentusa.com